

## PK15

Chaudière à granulés

Gris Clair/Gris  
Foncé

kW-N (min-max)	4,1 - 15,0
kW-H <sub>2</sub> O (min-max)	4,1 - 15,0
% (min-max)	88 - 93
m <sup>3</sup>	431
kg/h (min-max)	1,0 - 3,4
Dim.LxHxP	822 x 1398 x 745
kg	295
Ø mm	100 S/P/Lat.G
W (min-max)	20 - 25
kg/L	75 / 119
bar	3



## PR30

Chaudière à granulés avec extracteur de cendres

Gris Clair/Gris  
Foncé

kW-N (min-max)	8,9 - 30,0
kW-H <sub>2</sub> O (min-max)	8,9 - 30,0
% (min-max)	93 - 92
m <sup>3</sup>	861
kg/h (min-max)	2,0 - 6,8
Dim.LxHxP	892 x 1398 x 817
kg	325
Ø mm	120 S/P/Lat.G
W (min-max)	27 - 45
kg/L	75 / 119
bar	3



## PK20

Chaudière à granulés

Gris Clair/Gris  
Foncé

kW-N (min-max)	5,7 - 20,0
kW-H <sub>2</sub> O (min-max)	5,7 - 20,0
% (min-max)	88 - 92
m <sup>3</sup>	574
kg/h (min-max)	1,4 - 4,6
Dim.LxHxP	822 x 1398 x 745
kg	295
Ø mm	100 S/P/Lat.G
W (min-max)	20 - 25
kg/L	75 / 119
bar	3



## PR20

Chaudière à granulés avec extracteur de cendres

Gris Clair/Gris  
Foncé

kW-N (min-max)	5,7 - 20,0
kW-H <sub>2</sub> O (min-max)	5,7 - 20,0
% (min-max)	88 - 92
m <sup>3</sup>	574
kg/h (min-max)	1,4 - 4,6
Dim.LxHxP	822 x 1398 x 817
kg	310
Ø mm	100 S/P/Lat.G
W (min-max)	20 - 25
kg/L	75 / 119
bar	3



## PK30

Chaudière à granulés

Gris Clair/Gris  
Foncé

kW-N (min-max)	8,9 - 30,0
kW-H <sub>2</sub> O (min-max)	8,9 - 30,0
% (min-max)	93 - 92
m <sup>3</sup>	861
kg/h (min-max)	2,0 - 6,8
Dim.LxHxP	892 x 1398 x 745
kg	310
Ø mm	120 S/P/Lat.G
W (min-max)	27 - 45
kg/L	75 / 119
bar	3

